

X-50



The Thermal-Eye X-50 sets the standard for affordable, small, lightweight thermal imaging cameras. It is pocket-sized, rugged and durable. Based on the X200xp, the X-50 is perfect for public safety, first responder and security operations.



TARGET LOCATION

FORCE PROTECTION

ROUTINE PATROLS

SEARCH & RESCUE

DISTURBED SURFACES

COVERT SURVEILLANCE

FUGITIVE PURSUIT

OFFICER SAFETY

BENEFITS:

- Advanced technology made more affordable
- Stows easily in pocket for quick extraction in the field and on the run
- Unaffected by bright lights, glare or shadows, unlike traditional night vision technology
- Simple to use and operate, with covert eye cup and variable display brightness
- Designed to withstand 6ft (2m) drop to concrete

FEATURES:

- Developed with advanced amorphous silicon microbolometer technology
- Rugged design with integral rubber eye cup can survive accidental drops and underwater submersion to 9ft (3m)
- Pocket-sized, weighing only 13 ounces (0.38kg)
- Detects human activity from more than 1000ft (300m) away
- Two commercial AA batteries provide operating life of 5 hours (lithium) or 2 hours (alkaline)



Routine patrol in alley



Fugitive in pursuit



Covert surveillance



Summit Night Vision Group LLC, Fort Worth, Texas, USA
Summit Night Vision Group is a U.S. Service-Disabled, Veteran-Owned Small Business.
Summit Night Vision Sales: 817-475-0142 Sales@SummitNightVision.com



communications
Electro-Optical Systems

X-50 TECHNICAL SPECIFICATIONS:

FEATURES		THERMAL-EYE X-50			
FOCAL PLANE ARRAY	MATERIAL & STRUCTURE	Amorphous Silicon Microbolometer			
	PIXEL COUNT (RESOLUTION)	100 x 80			
	SPECTRAL RESPONSE	7-14µm (filter bandwidth)			
	THERMAL SENSITIVITY	≤150 mK			
THERMAL IMAGING PERFORMANCE	START-UP TIME	~ 5 seconds			
	BRIGHTNESS/CONTRAST	Fully automatic			
	RANGE TO DETECT HUMAN ACTIVITY	Up to 1000ft (305m)			
	SUSCEPTIBILITY TO BLINDING VISIBLE LIGHT	None			
	INFRARED POLARITY	White Hot			
OPTICS	FOV (H x V)	11° x 8°			
	FOCUS METHOD	Manual			
	MINIMUM FOCUS DISTANCE	~ 3ft (1m)			
VIDEO	OUTPUT FORMAT	Analog: NTSC or PAL monochrome on rear outlet jack			
	VIEWFINDER DISPLAY	Monochrome LCD (320 x 240 pixels)			
	VIEWFINDER DIMMING	Integral to power on/off switch			
POWER	POWER SOURCE	2 AA batteries			
	OPERATING TIME	~ 2 hours with alkaline ~5 hours with lithium [77°F (25°C), nighttime operation]			
	AUXILIARY POWER	9 to 12 VDC input on rear outlet jack			
ENVIRONMENTAL CHARACTERISTICS	OPERATING TEMPERATURE	+14°F to 122°F (-10°C to 50°C)			
	STORAGE TEMPERATURE	-4°F to 176°F (-20°C to 80°C)			
	WATER & SHOCK RESISTANCE	Waterproof to 9ft (3m) submersion, buoyant in water. Shockproof to 6ft (2m) drop.			
	EMC COMPLIANCE	FCC Part 15 & CE Mark			
PHYSICAL CHARACTERISTICS	SIZE	5-1/4" L x 4-1/2" W x 2" H (13.4 x 11.4 x 5.1cm)			
	WEIGHT	13oz (381g), batteries installed			
	EYE CUP	Integral to camera body with 2" eye relief			
ORDERING INFORMATION	CAMERA PART NUMBERS	NTSC: 1000380-0001			
		PAL: 1000380-0002			
CAMERA FEATURES		<ul style="list-style-type: none"> - On-screen battery level indicator - Left- or right-hand operation with rugged slip-resistant grip - 1/4-20 tripod mount - Tactile battery loading feature for stealth nighttime operation - External video and power jacks - Long eye-relief viewfinder for use with glasses, face shield, masks, etc. 			
STANDARD EQUIPMENT		<ul style="list-style-type: none"> - 2 AA alkaline batteries - Neck strap & wrist strap - Lens cover - Lens cleaning cloth 			
OPTIONAL EQUIPMENT	OPTIONAL EQUIPMENT	Hard protective case	Power cable (12VDC)	Video cable	AC power adapter
	PART NUMBER	CD11388	6458-1	7070409-0001	6453-1

Specifications subject to change without notice

X-50 January 2010

This material is L-3 Infrared Products general capabilities information and does not contain any controlled technical data as defined within the International Traffic in Arms Regulations (ITAR) or Export Administration Regulations (EAR).



Summit Night Vision Group LLC, Fort Worth, Texas, USA
 Summit Night Vision Group is a U.S. Service-Disabled, Veteran-Owned Small Business.
 Summit Night Vision Sales: 817-475-0142 Sales@SummitNightVision.com

